









REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		Initial release	/	SGF

Note:

1. Material:
  - 1.1 Housing: LCP
  - 1.2 Contact: C7025, t~0.20mm
  - 1.3 Shell: SUS316
2. ELECTRICAL:
  - 2-1: CURRENT RATING:  
VBUS AND GND CONTACTS RATED AT 1.25A PARALLELED FOR A TOTAL OF 5A;
  - 2-2: INITIAL CONTACT RESISTANCE :40 MEGOHMS
  - 2-3: DIELECTRIC WITHSTANDING VOLTAGE:  
100V AC MIN;
3. MECHANICAL CHARACTERISTICS:
  - 3-1: MATING FORCE: 5~20N
  - 3-2: UNMATING FORCE: 8~20N (INITIAL),  
6~20N (AFTER 10000 CYCLES)
  - 3-3: FREQUENCY: 200±50 CYCLES / HOUR,  
10000 CYCLES
  - 3-4: OPERATING TEMPERATURE ; -40°~80°.



RECOMMENDED P.C.B. LAYOUT (T:1.00mm)  
TOLERANCE UNSPECIFIED ±0.05mm




THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		<b>深圳市步步精科技有限公司</b>	
PDWG.NO: 0366-2		NAME: TYPE-C 16P 防水母座 直立式 四脚插 带柱 端子SMT 双筋位 外壳粉末冶金 IPX7 0型防水圈 H=7.5 编带	
APPD.	JM_Zheng	PJ. NO.: 126-224-160004-N5G	
CHKD.	LYX	SIZE: A4 DRW NO.:	
DR.	SGF	FINISH: SEE NOTES	MAT'L.: SEE NOTES
		SCALE: N/A	REV.: A0
		UNIT: mm	PAGE: 1/3

USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
<del>A2</del>	<del>TXp1</del>	<del>B11</del>	<del>RXp1</del>
<del>A3</del>	<del>TXn1</del>	<del>B10</del>	<del>RXn1</del>
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
<del>A10</del>	<del>RXn2</del>	<del>B3</del>	<del>TXn2</del>
<del>A11</del>	<del>RXp2</del>	<del>B2</del>	<del>TXp2</del>
A12	GND	B1	GND

Suggested adsorption size




Added suction cover view




THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
OR IN PART WITHOUT  
PRIOR WRITTEN PERMISSION.  
PDWG.NO: 0366-2

深圳市步步精科技有限公司	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X': ±3' .X': ±2' .XX': ±1'
APPD. JM_Zheng CHKD. LYX DR. SGF	NAME: TYPE-C 16P 防水母座 直立式 四脚插 带柱 端子SMT 双筋位 外壳粉末冶金 IPX7 0型防水圈 H=7.5 编带 PJ. NO.: 126-224-160004-N5G SIZE: A4 DRW NO.: FINISH: SEE NOTES MAT'L.: SEE NOTES SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/3


REV.	ECN NO	CONTENT	DATE	ENGINEER
A0		Initial release	/	SGF




① 产品入载带示意图




② 卷盘贴标签示意图



⑤ 外箱封箱示意图



④ 产品入外箱示意图



③ 7盘产品叠层示意图



	REEL	CARTON
CONNECTOR (PCS)	500	3500

- 包装说明:
1. 将检验好的成品;对插口朝前放入载带;每卷装500PCS产品;具体如图一所示
  2. 将包装好的产品;每盘必需贴上内标签;具体如图二所示
  3. 将贴好内标签的产品每7盘叠;具体如图三所示
  5. 装好后并封好纸箱及贴好相关标签;具体如图五所示;  
(产品包装的标签,如客户有要求,请按客户要求包装出货)
  6. 载带前面留17PCS空格,后面留17PCS空格
  7. COVER与CARRY剥离力:50-125g,速度:300mm/分钟左右,剥离角度:165°-180°



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		<b>深圳市步步精科技有限公司</b>	
PDWG.NO: 0366-2		.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X': ±3" .X': ±2" .XX': ±1"
APPD.	JM_Zheng	NAME: TYPE-C 16P 防水母座 直立式 四脚插 带柱 端子SMT 双筋位 外壳粉末冶金 IPX7 0型防水圈 H=7.5 编带	
CHKD.	LYX	PJ. NO.: 126-224-160004-N5G	
DR.	SGF	SIZE: A4 DRW NO.:	
		FINISH: SEE NOTES	MAT'L.: SEE NOTES
		SCALE: N/A	REV.: A0
		UNIT: mm	PAGE: 3/3