


机壳与胶圈干涉建议单边0.15最小, 胶圈尺寸跑上限








组装示意图


开孔尺寸参考

组装外壳时需要打环保润滑油


胶圈使用尺寸参考图



RECOMMENDED P.C.B. LAYOUT (T:1.00mm)
TOLERANCE UNSPECIFIED ±0.05mm



Suggested adsorption size



Added suction cover view




A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME


THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.
PDWG.NO: 0366-2

深圳市步步精科技有限公司		NAME: TYPE-C 24P 防水母座 直立式 四脚插 带柱 端子SMT 双筋位 外壳粉末冶金 IPX7 0型防水圈 H=6.68 编带	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X': ±3' .X': ±2' .XX': ±1'	PJ. NO.: 126-224-240003-N5G	SIZE: A4 DRW NO.:
APPD. JM_Zheng	CHKD. LYX	FINISH: SEE NOTES	MAT'L: SEE NOTES
DR. SGF	SCALE: N/A	REV.: A0	UNIT: mm
		PAGE: 1/2	


REV.	ECN NO	CONTENT	DATE	ENGINEER
A0		Initial release	/	SGF




① 产品入载带示意图




⑤ 外箱封箱示意图



④ 产品入外箱示意图



② 卷盘贴标签示意图



③ 7盘产品叠层示意图



	REEL	CARTON
CONNECTOR (PCS)	550	3850

包装说明:

1. 将检验好的成品;对插口朝前放入载带;每卷装550PCS产品;具体如图一所示
2. 将包装好的产品;每盘必需贴上内标签;具体如图二所示
3. 将贴好内标签的产品每7盘叠;具体如图三所示
5. 装好后并封好纸箱及贴好相关标签;具体如图五所示;
(产品包装的标签,如客户有要求,请按客户要求包装出货)
6. 载带前面留17PCS空格,后面留17PCS空格
7. COVER与CARRY剥离力:50-125g,速度:300mm/分钟左右,
剥离角度:165° -180°



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION. PDWG.NO: 0366-2		深圳市步步精科技有限公司		NAME: TYPE-C 24P 防水母座 直立式 四脚插 带柱 端子SMT 双筋位 外壳粉末冶金 1PX7 0型防水圈 H=6.68 编带	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X': ±3' .X': ±2' .XX': ±1'	APPD.	JM_Zheng	PJ. NO.:	126-224-240003-N5G
CHKD.	LYX	SIZE:	A4	DRW NO.:	
DR.	SGF	FINISH:	SEE NOTES	MAT'L:	SEE NOTES
SCALE:	N/A	REV.:	A0	UNIT:	mm
PAGE:	2/2				