





REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		INITIAL RELEASE	2024 12/10	Yan

NOTES:

- 电气特性:
耐压: 100V AC/60S/0.5mA
绝缘阻抗: 100MΩ/MIN,500V DC/MIN
接触阻抗: 40mΩ/MAX(VBUS/GND)测试后变化10mΩ;
额定电流: 2A 温度: 30°/MAX
- 机械物性:
插入力: 5~20N
拔出力: 8~20N,测试后拔出力6~20N;
耐久次数: 10000次
- 产品物料及制程符合“Rohs”文件对环境管理标准。



PIN DEFINE

PIN DEFINE		PIN DEFINE			
CONN PIN	PCB PIN	pin	Signal Name	Description	Mating Sequence
B4 B9(VBUS)	P1正极	B1	GND	Ground return	First
B1 B12(GND)	P4负极	B4	VBUS	Bus Power	First
		B9	VBUS	Bus Power	First
		B12	CC1	Ground return	First

5	中夹片	1 PCS	SUS301
4	MOLDING密封圈	1 PCS	TPE,BLACK,60度
3	MOLD 2	1 PCS	PA10T,BLACK
2	MOLD 1	1 PCS	PA46,BLACK
1	Terminal	1 PCS	C7025 T=0.2mm,Au:1u",Sn:80u"
序号	零件	数量	规格

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.

PDWG,NO: 9999-9

DR. Yan 2024/12/10

深圳市步步精科技有限公司

NAME: TYPE C 4P 防水 线端 带凸台

P/N.: 126-229-040001-00G


SIZE: A4 DRW NO.: CC24-0003

FINISH: SEE NOTES MAT'L.: SEE NOTES

SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2


REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		INITIAL RELEASE	2024 12/10	Yan

PE袋规格: 260*185



纸箱

成品标签



1. 包装要求:
- 1.1 每个PE袋包装1000pcs;
 - 1.2 每15袋一个纸箱, 共计15000pcs;
 - 1.3 纸箱外贴上标签

纸箱规格: 33.5*33.5*19CM



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		 深圳市步步精科技有限公司	
PDWG:NO: 9999-9		.X: ±0.38 .XX: ±0.25 .XXX: ±0.13	X': ±3" .X': ±2" .XX': ±1"
APPD.		NAME: TYPE C 4P 防水 线端 带凸台	
CHKD.		PJ. NO.:126-229-04001-00G SIZE: A4 DRW NO.: CC24-0003	
DR.	Yan 2024/12/10	FINISH: SEE NOTES	MAT'L.: SEE NOTES
		SCALE: N/A	REV.: A1 UNIT: mm PAGE: 2/2