





REV.	ECN NO	CONTENT	DATE	ENGINEER
A0				

规格:


1. 额定值: DC30V 0.5A
2. 接触电阻: $\leq 30\text{m}\Omega$
3. 绝缘电阻: $\geq 100\text{M}\Omega$
4. 耐电压: 500VAC
5. 插拔力: 3N~30N
6. 使用寿命: 5000次
7. 使用温度: $-20^{\circ}\text{C}\sim+80^{\circ}\text{C}$



P.C.B 设计参考尺寸



推荐插头尺寸



电路示意图




6	后盖	PA66	1	黑色
5	主体	PA66	1	黑色
4	平片	黄铜 T=0.3mm	1	镀铜锡
3	弯片	黄铜 T=0.3mm	1	镀铜锡
2	弹片	磷铜 T=0.2mm	1	镀铜锡
1	PIN针	黄铜	1	镀铜锡
序号	名称	材料	数量	颜色/电镀


THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.
PDWG.NO: 0050-2

.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13		X*: $\pm 3^{\circ}$.X*: $\pm 2^{\circ}$.XX*: $\pm 1^{\circ}$		NAME: DC插座 DC-005 2.5针 全铜	
APPD.	JM_Zheng	PJ. NO.: DC.02.72-11-2001		SIZE: A4 DRW NO.:	
CHKD.	LYX	FINISH: SEE NOTES		MAT'L.: SEE NOTES	
DR.	TSP	SCALE: N/A		REV.: A0	UNIT: mm
				PAGE: 1/2	

PE袋规格: 260*185



成品标签



1. 包装要求:

- 1.1 每个PE袋包装500pcs;
- 1.2 每1袋放一小纸盒;
- 1.3 每20个小纸盒放一个纸箱, 共计10000pcs;
- 1.4 纸箱外贴上标签



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13		NAME: DC插座 DC-005 2.5针 全铜	
APPD.	JM_Zheng	PJ. NO.: DC.02.72-11-2001	
CHKD.	LYX	SIZE: A4 DRW NO.:	
PDWG.NO:	0050-2	FINISH: SEE NOTES	MAT'L.: SEE NOTES
DR. TSP		SCALE: N/A	REV.: A0 UNIT: mm PAGE: 2/2