

REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0		Initial release	/	GZY

NOTES:

1. MATERIAL:

- 1-1 HOUSING:LCP WITH 30% G/F UL 94V-0 COLOR:BLACK.
- 1-2 CAP:LCP WITH 30% G/F UL 94V-0 COLOR:BLACK.
- 1-3 TERMINAL:COPPER ALLOY T=0.20mm
- 1-4 SHELL:SPCC T=0.50mm

2. PLATING:

2-1 TERMINAL:

GOLD PLATED ON CONTACT AREA
AND 100μ" MIN. MATTE-TIN ON SOLDER TAIL,
WITH ENTIRE CONTACT UNDERPLATED 80μ" MIN. NICKEL.

2-2 SHELL:50μ" MIN. NICKEL PLATED.

3. MECHANICAL PERFORMANCE

- 3-1 INSERTION FORCE: 4.5kgf MAX
- REMOVAL FORCE: 1kgf MIN; 4.0kgf MAX
- DURABKLITY:5000 CYCLES

4. ELECTRICAL PERFORMANCE:


- 4-1 Current Rating: 0.5A
- 4-2 Voltage Rating: 40V AC
- 4-3 CONTACT RESISTANC:INITIAL 30mΩ MAX.
AFTER TEST:Δ10 mΩ MAX
- 4-4 DIELECTRIC STRENGTH:UNMATED CONNECTORS APPLY 500V AC
MATED CONNECTOR APPLY 300V AC
- 4-5 INSULATION RESISTANCE:100 MEGAOHMS MIN. (UNMATED)
10 MEGAOHM° S MIN. (MATED)

5. ENVIRONMENTAL PERFORMANCE:

- OPERATING TEMPERATURE: -25° C~+85° C
- SALT SPRAY:24H



PIN	Signal Assignment	PIN	Signal Assignment
1	TMDS Data2+	2	TMDS Data2 Shield
3	TMDS Data2-	4	TMDS Data1+
5	TMDS Data1 Shield	6	TMDS Data1-
7	TMDS Data0+	8	TMDS Data0 Shield
9	TMDS Data0-	10	TMDS Clock+
11	TMDS Clock Shield	12	TMDS Clock-
13	CEC	14	Utility
15	SCL	16	SDA
17	DDC/CEC Ground	18	+5V Power
19	Hot Plug Detect		



THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.

PDWG,NO: 0100-2



深圳市步步精科技有限公司

.X: ±0.38 .X': ±3"
.XX: ±0.25 .X': ±2"
.XXX: ±0.13 .XX': ±1"

NAME: HDMI 19P 2.1版 母座 直立式 外壳三脚DIP
端子SMT H=10.50 带侧弹 平口 铜壳 LCP黑色 加盖 编带

APPD. JM_Zheng PJ. NO.: 124-224-190002-V2G
CHKD. LYX SIZE: A4 DRW NO.:
FINISH: SEE NOTES MAT'L.: SEE NOTES
DR. GZY SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2

REV.	ECN NO	CONTENT	DATE	ENGINEER
A0		Initial release	/	GZY




NO. 1

NOTES

1. 帶子引導長度
LEAD TAPE LENGTH
出料方向
PULL OUT DIRECTEON



出料方向
PULL OUT DIRECTEON




纸箱规格: 39*39*38cm

NO. 4

2. 上帶 剥力力為: 0.1~1.3N(10.2gf~130gf)
PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)
出貨運輸過程中一定注意:
THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:
卷帶在運輸過程中不能散開
PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION



NO. 3



NO. 2



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.				深圳市步步精科技有限公司			
.X: ±0.38	.X': ±3"	NAME: HDMI 19P 2.1版 母座 直立式 外壳三脚DIP		端子SMT H=10.50 带侧弹 平口 铜壳 LCP黑色 加盖 编带			
.XX: ±0.25	.X': ±2"	APPD. JM_Zheng		PJ. NO.: 124-224-190002-V2G			
.XXX: ±0.13	.XX': ±1"	CHKD. LYX		SIZE: A4 DRW NO.:			
PDWG.NO: 0100-2		DR. GZY		FINISH: SEE NOTES		MAT'L.: SEE NOTES	
				SCALE: N/A		REV.: A0	
				UNIT: mm		PAGE: 2/2	