


REV.	ECN NO	CONTENT	DATE	ENGINEER
A0				

NOTES:

1. MATERIAL:
HOUSING: LCP, BK, UL 94V-0
SHELL: SPCC/BRASS
TERMINAL: C2680-EH
2. CONTACT PLATING:
50u" Min NICKEL UNDERPLATING OVER ALL
GOLD PLATING AT CONTACT AREA (SEE P/N)
80u" Min TIN AT SOLDERING AREA
SHELL PLATING: NICKEL 50U" Min
3. ELECTRICAL:
INSULATION RESISTANCE: 100MΩ MIN
CONTACT RESISTANCE: 30mΩ MAX
DIELECTRIC WITHSTAND: 500 VAC FOR 1Min
CURRENT RATING: 0.5A
VOLTAGE RATING: 40V
4. MECHANICAL:
INSERTION FORCE: 4.5 KGF MAX
WITHDRAWAL FORCE: 1.0~4.0 KGF
5. DURABILITY: 10000 CYCLES
6. TEMPERATURE RANGE: -55°C TO +105°C




RECOMMENDED P.C.B HOLE LAYOUT
COMPONENT SIDE VIEW (TOLERANCE: +/−0.05)

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司		NAME: HDMI 19P A型 母座 L=11.60 板上四脚插 平口 铜壳镀镍 带凸点 端子SMT 内控印字 热封编带	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X': ±3' X'': ±2' X'X': ±1'		APPD. JM_Zheng CHKD. LYX DR. TSP	
PDWG. NO: 0100-2		PJ. NO.: HD.01.51-21-1002 SIZE: A4 DRW NO.: FINISH: SEE NOTES SCALE: N/A		MAT'L.: SEE NOTES REV.: A0 UNIT: mm PAGE: 1/3	


REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0				

外壳脚规格:

规格	DIM A	DIM B	外壳脚凸点
1	2.16	1.66	无凸点
2	2.16	1.66	带凸点
3	1.50	1.50	无凸点
4	2.20	2.20	无凸点
5	1.50	1.50	带凸点





脚有凸点




脚无凸点




THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13		NAME: HDMI 19P A型 母座 L=11.60 板上四脚插 平口 铜壳镀镍 带凸点 端子SMT 内控印字 热封编带	
APPD.	JM_Zheng	PJ. NO.: HD.01.51-21-1002	
CHKD.	LYX	SIZE: A4 DRW NO.:	
PDWG.NO:	0100-2	DR.	TSP
		FINISH: SEE NOTES	MAT'L.: SEE NOTES
		SCALE: N/A	REV.: A0 UNIT: mm PAGE: 2/3



NO. 1




NO. 2



纸箱规格: 33*33*30.5cm

NO. 4



NO. 3



1. 包装要求:
- 1.1 每卷包装500pcs, 卷带前后各空出5pcs位置;
 - 1.2 每10盘放一箱, 共计5kset;
 - 1.3 纸箱外贴上标签

备注:

1. 若有未装满之零数, 必须用泡棉塞满。
2. 针对于包装方式可根据客户要求包装。

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X*: ±3" .X*: ±2" .XX*: ±1"	
APPD. JM_Zheng		NAME: HDMI 19P A型 母座 L=11.60 板上四脚插 平口 铜壳电镀 带凸点 端子SMT 内控印字 热封编带	
CHKD. LYX		PJ. NO.: HD.01.51-21-1002	
DR. TSP		SIZE: A4 DRW NO.:	
PDWG.NO: 0100-2		FINISH: SEE NOTES MAT'L.: SEE NOTES	
		SCALE: N/A REV.: A0 UNIT: mm PAGE: 3/3	