







REV	ECN	NO	CONTENT	DATE	ENGINEER
A0			INITIAL RELEASE	/	SGF

NOTES:

- 1.Material:SEE TABLE1;
- 2.Plating specification,
- 2-1.Contact:  
Contact area: Ni50u"Min/Au3u";  
Solder area: Ni50u"Min/Sn100u"Min.  
Other area: Ni 50u"Min.
- 2-2.Shell: Ni50u"~150u";
- 2-3.Latch:  
Solder area: Ni50u"Min/Sn100u"Min.  
Other area: Ni 50u"Min.
- 3.Mechanic Performance ,  
3-1.Insertion Force:5~20N;  
3-2.Extraction Force:8~20N after 10000 cycles;  
3-3.Durability:10000 cycles.
- 4.Electrical Performance,  
4-1.Insulation Resistance:100MΩ Min.  
4-2.Contact Resistance <50mΩ Max.  
4-3.Dielectric Strength :100V AC.  
4-4.Contact current rating: 3.75A/Pin for vbus  
and gnd, 1.8A/Pin for all other contact.
- 5.Use Specification:  
5-1. Voltage : 20V (DC)  
5-2. Current : 15A
- 6.The product accords with ROHS STD.
- 7.Operating temperature:-40°C~85°C.



RECOMMENDED P.C.B. LAYOUT  
TOLERANCE UNSPECIFIED ±0.05mm



THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
PRIOR WRITTEN PERMISSION.  
PDWG NO:0366-2



APPD	JM_Zheng	PJ NO:
CHKD	LYX	SIZE:A DRW NO:
		FINISH:SEE NOTES MAT'L:SEE NOTES
		SCALE:N/A REV:A0 UNIT:mm PAGE:1/2

X: ±0.38 X: ±3 NAME: TYPE-C 16P 母座 板上四脚插 脚长0.9 端子  
.XX: ±0.25 .X: ±2 SMT 带柱 L=7.35 PA10T 蓝胶 大电流15A 编带  
.XXX: ±0.13 .XX: ±1

APPD JM\_Zheng PJ NO:  
CHKD LYX SIZE:A DRW NO:  
FINISH:SEE NOTES MAT'L:SEE NOTES  
SCALE:N/A REV:A0 UNIT:mm PAGE:1/2



包材组成用量

卷装示意图


1	载带	PET	W=16mm T=0.35mm	10
2	上带	PET	W=12.7mm T=0.05mm	10
3	盘面标签			1
4	卷盘	PS	Ø330MM*W20.5MM	10
5	载带保护带			1
6	天地板	B=B	L320mm*W320mm	2
7	三角柱	B=B	L290mm*W210mm	4
8	外箱	K=K	L340mm*W340mm*325mm	1
9	外标签			1
ITEM	描述	材质	规格	用量



- 卷装注意事项:
1. 上带不可盖住载带棘轮孔,且不可超出载带边缘
  2. 产品包在载带中不可放反,产品不可超出载带高度
  3. 载带轻轻翻转过来,产品能自由落下不卡产品
  4. 包装后载带及上带不可有破损,折皱等不良
  5. 盘面标签统一朝载带圆孔的另一面
  6. 上带拨离力: 40~100gf

序号	每盘数量	每箱数量
1	1000	10000

装箱示意图



THIS DOCUMENT IS THE  
SOLE PROPERTY OF  
BBJconn Technology Co.,Ltd.  
Corporation AND SHOULD  
NOT BE USED IN WHOLE  
PRIOR WRITTEN PERMISSION.  
PDWG NO: 0366-2

**JB** 深圳市步步精科技有限公司

.X: ±0.38	X': ±3°	NAME: TYPE-C 16P 母座 板上四脚插 脚长0.9 端子
.XX: ±0.25	.X': ±2°	SMT 带柱 L=7.35 PA10T蓝胶 大电流15A 编带
.XXX: ±0.13	.XX': ±1°	
APPD	JM_Zheng	PJ NO: SIZE:A4 DRW NO:
CHKD	LYX	FINISH:SEE NOTES MAT'L:SEE NOTES
DR	SGF	SCALE:N/A REV:A0 UNIT:mm PAGE:2/2