









RECOMMENDED P.C.B. LAYOUT (T:1.00mm)

TOLERANCE UNSPECIFIED $\pm 0.05\text{mm}$ 

剖视图



剖视图



REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0				

特性:

一、电气性能: ELECTRICAL

1. 额定电流: 5.0A
2. 接触阻抗: 40 MILLIOHMS MAX
3. 耐电压: 150V AC / 1 mA MAX
4. 绝缘阻抗: 150V DC/100 MEGA OHMS MIN

二、机械性能:

- 1.插入力: 5~20N
- 2.拨出力: 8~20N
- 3.使用寿命: 10000次、拨出力 6N MIN

三、材料: MATERIAL

1. 塑胶: LCP/PA9T UL94V-0
2. 端子: C7025/C18400 T=0.15MM
3. 外壳: SUS304 T=0.30MM
4. 卡勾: SUS304 T=0.20MM

四、电镀:FINISH

1. 端子: 接触点镀金3U"MIN
PIN脚焊接区域镀金1U"MIN.
2. 外壳: 镀镍50U"MIN (盐雾48H)

五、电镀品需做粘锡测试：粘锡面积达到95%以上。

六、SMT回流焊（峰值 $260^{\circ}\text{C}\pm 5^{\circ}\text{C}$ ）不能起

熔胶、变色不良(变形在公差范围以内)

七、工作温度： $-40^{\circ}\text{C}\sim+85^{\circ}\text{C}$

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B7	D-
A6	D+	B6	D+
A7	D-	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD

NOT BE USED IN WHOLE

OR IN PART WITHOUT

PRIOR WRITTEN PERMISSION.

First Name: _____



深圳市步步精科技有限公司

.X: ± 0.38	X*: $\pm 3^*$
.XX: ± 0.25	.X*: $\pm 2^*$
.XXX: ± 0.13	.XX*: $\pm 1^*$

APRD	IM Zheng
------	----------

AFFID.	JM_Zheng

CHKD. LYX

DB	TCD
----	-----

NAME:

TYPE-C 14P 母座 直立式 H=9.30 舌片外漏0.27 四脚插 端子DIP



P.I NO : 126-225-140003-N5G


NO. NO.: 120-225-140003-N30
SIZE: M DRW. NO.:

FINISH	SEE NOTES	MAT'L	SEE NOTES
--------	-----------	-------	-----------

FINISH: SEE NOTES		MAT'L: SEE NOTES	
CONT. NO.	REV.	DATE	BY




REV.	ECN NO.	CONTENT	DATE	ENGINEER
A0				






① PE真空盒 (1Set).

② 100Pcs/盒,



③ 50盒/箱 (5k).

外箱物料标签



⑥ 依图示粘贴产品或ROHS标签.

- 备注:
1. PE真空盒1set
 2. 每盒装成品100Pcs
 3. 每箱数量见表一
 4. 外箱尺寸与规格: 36*20*28CM
 5. 外箱用透明胶纸带封"工"字型;



⑤ 外箱用透明胶纸带封"工"字型.

④ 每箱竖放25盒*2, 若尾数箱在空间处加装填充物.

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.				深圳市步步精科技有限公司			
.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13		X': $\pm 3'$ X'': $\pm 2'$ XX': $\pm 1'$		NAME: TYPE-C 14P 母座 直立式 H=9.30 舌片外漏0.27 四脚插 端子DIP			
APPD. JM_Zheng		CHKD. LYX		PJ. NO.: 126-225-140003-N5G			
PDWG.NO: 0366-2		DR. TSP		SIZE: A4 DRW NO.:			
				FINISH: SEE NOTES MAT'L.: SEE NOTES			
				SCALE: N/A REV.: A0 UNIT: mm PAGE: 2/2			